

TOSHIBA Bipolar Linear Integrated Circuit Silicon Monolithic

TA2069AFG


3V Stereo Headphone Amplifier (3V USE)

The TA2069AFG is developed for play-back stereo headphone equipments (3V use).

It is built in dual preamplifiers, dual OCL power amplifiers, motor governor, DC volume control and volume limiter etc.

Features

- Built-in preamplifier
Input coupling condenser-less
Built-in input capacitor for reducing buzz noise
Low noise: $V_{ni} = 1.2 \mu V_{rms}$ (typ.)
- Built-in power amplifier
OCL (output condenser-less)
Voltage gain : $G_V = 31dB$ (typ.)
- Built-in motor governor
Current proportion type
- Built-in DC volume control function
DC volume maximum attenuation : $ATT = 82dB$ (typ.)
- Built-in volume limiter function
- Built-in bass boost function
- Operating supply voltage range ($T_a = 25^\circ C$)
PRE + PW: $V_{CC} (opr) = 1.8 \sim 3.6V$
GVN: $V_{CC} (opr) = 2.1 \sim 3.6V$ (motor voltage = 1.8V)
- Low supply current ($V_{CC} = 3V$, $f = 1kHz$, $T_a = 25^\circ C$, typ.)
PRE + PW




Weight: 0.32g (typ.)

	No Signal	Output Power	
		0.1mW × 2	0.5mW × 2
R _L = 16Ω	9.5mA	14.2mA	19.5mA
R _L = 32Ω	9.5mA	12.5mA	16.5mA

GVN: ICC = 2.5mA

Block Diagram



Terminal Voltage: Typical terminal voltage at no signal with test circuit

Terminal		Function	Internal Circuit	Terminal Voltage (V)
No.	Name			
1	PRE GND	The GND, except for power drive stage and motor governor stage.	—	0
2	IN _A	Input of preamplifier		1.2
23	IN _B			1.2
3	NF _A	NF of preamplifier		1.2
22	NF _B			1.2
4	PRE OUT _A	Output of preamplifier		1.2
21	PRE OUT _B			1.2
5	PW IN _A	Input of power amplifier		1.2
20	PW IN _B			1.2
6	V _{CTL}	The terminal of DC volume control • This terminal can be used also for V _{LIM} terminal.		—
18	V _{LIM}	The terminal of volume limiter level control • This terminal can be used also for V _{CTL} terminal.		—
7	OUT _B	Output of power amplifier		1.2
8	OUT _A			
9	OUT _C			

2004-12-01

Application Note

1. VCC and GND

This IC has two VCC terminals and three GND terminals. Pattern layout should be designed carefully to reduce the common impedance.

VCC

VCC (pin 17): Preamplifier stage and power amplifier stage.

GVN VCC (pin 16): Motor governor stage.

GND

PRE GND (pin 1): Preamplifier stage and power amplifier stage except the power drive stage.

PW GND (pin 11): Power drive stage of power amplifier.

GVN GND (pin 12): Motor governor stage.

2. VREF

It is necessary to stabilize the VREF circuit, the internal circuit operate on this reference.

3. Preamplifier

Input signal should be applied to VREF standard, otherwise pop noise become bigger when VCC is turned on and off.

4. Power amplifier

It is necessary to insert the coupling capacitor through the PW IN terminal. In case that DC current or DC voltage is applied to the PW IN terminal, the internal circuit has unbalance and the power amplifier doesn't operate normally.

Maximum Ratings (Ta = 25°C)

Characteristic	Symbol	Rating	Unit
Supply voltage	V _{CC}	4	V
Power dissipation	P _D	(Note 1)	mW
		(Note 2)	
Output current (PW AMP.)	I _O (PW)	200	mA
Output current (GVN)	I _O (GVN)	700	mA
Operating temperature	T _{opr}	-25~75	°C
Storage temperature	T _{stg}	-55~150	°C

Note 1: IC only: Derated above Ta = 25°C in the proportion 3.2 mW/°C

Note 2: IC + PCB (TOSHIBA typical PCB): Derated above Ta = 25°C in the proportion 7.4 mW/°C

Electrical Characteristics

Unless otherwise specified, $V_{CC} = 3V$, $T_a = 25^\circ C$, $f = 1kHz$, SW2: a, SW5: a


Preamplifier: $R_g = 2.2k\Omega$, $R_L = 10k\Omega$, SW1: ON, SW3: b, SW4: b

Power amplifier: $R_g = 600\Omega$, $R_L = 16\Omega$, Vol: Max, SW1: OPEN, SW3: a, SW4: a

Motor governor: $I_m = 100mA$, SW1: OPEN, SW3: b, SW4: b

Characteristic	Symbol	Test Circuit	Test Condition	Min	Typ.	Max	Unit
Quiescent supply current	I_{CCQ}	—	PRE + PW + GVN $V_{in} = 0$, VOL: Min, SW4: b	—	12	18	mA
Pre AMP.	Open loop voltage gain	G_{VO}	$V_O = -10dBV$, SW2: b	—	86	—	dB
	Closed loop voltage gain	G_{VC}	$V_O = -10dBV$	—	35	—	dB
	maximum output voltage	V_{om}	THD = 1%	550	720	—	mV _{rms}
	Total harmonic distortion	THD1	$V_O = -10dBV$	—	0.02	0.3	%
	Equivalent input noise voltage	V_{ni}	$R_g = 2.2k\Omega$, SW1: OPEN BPF = 20Hz~20kHz, NAB (G_V = 35dB, $f = 1kHz$)	—	1.2	2.4	μV_{rms}
	Cross talk	CT1	$V_O = -10dBV$	—	70	—	dB
	Ripple rejection ratio	RR1	$f_r = 100Hz$, $V_r = -20dBV$	—	48	—	dB
Power AMP.	Voltage gain 1	G_{V1}	$V_O = -10dBV$	29	31	33	dB
	Channel balance	CB		-1.5	0	+1.5	dB
	Voltage gain 2	G_{V2}	$V_O = -10dBV$, SW5: b	—	5	—	dB
	Output power 1	P_{O1}	$R_L = 16\Omega$, THD = 10%	17	28	—	mW
	Output power 2	P_{O2}	$R_L = 32\Omega$, THD = 10%	—	20	—	mW
	Total harmonic distortion	THD2	$P_O = 1mW$	—	0.5	—	%
	Output noise voltage 1	V_{no1}	$R_g = 600\Omega$, SW3: b BPF = 20Hz~20kHz	—	270	400	μV_{rms}
	Output noise voltage 2	V_{no2}	$R_g = 600\Omega$, SW3: b SW5: b, BPF = 20Hz~20kHz	—	45	—	μV_{rms}
	Ripple rejection ratio	RR2	$f_r = 100Hz$, $V_r = -20dBV$	—	52	—	dB
	Cross talk	CT2	$V_O = -10dBV$	—	32	—	dB
	DC volume maximum attenuation	ATT	$V_O = -10dBV$ SW4: a→b (VOL: Max→min)	—	82	—	dB
	Supply current	I_{CC}	$I_m = 0$	—	2.5	4.3	mA
Motor Governor	Saturation voltage	$V_{CE(sat)}$	$I_m = 200mA$	—	—	0.5	V
	Reference voltage	V_{REF}	$I_m = 100mA$	0.76	0.81	0.86	V
	Reference voltage fluctuation 1	ΔV_{REF1}	$V_{CC} = 2.1\sim 3.6V$	—	0.25	—	% / V
	Reference voltage fluctuation 2	ΔV_{REF2}	$I_m = 25\sim 250mA$	—	0.003	—	% / mA
	Reference voltage fluctuation 3	ΔV_{REF3}	$T_a = -25\sim 75^\circ C$	—	0.005	—	% / $^\circ C$
	Current ratio	K		34.5	37.5	40.5	
	Current ratio fluctuation 1	$\Delta K1$	$V_{CC} = 2.1\sim 3.6V$	—	0.25	—	% / V
	Current ratio fluctuation 2	$\Delta K2$	$I_m = 25\sim 250mA$	—	0.08	—	% / mA
	Current ratio fluctuation 3	$\Delta K3$	$T_a = -25\sim 75^\circ C$	—	0.005	—	% / $^\circ C$

Test Circuit



Characteristic Curves







Unless otherwise specified







$V_{CC} = 3V$, $T_a = 25^\circ C$, $f = 1kHz$







Preamplifier: $R_g = 2.2k\Omega$, $R_L = 10k\Omega$







Power amplifier: $R_g = 600\Omega$, $R_L = 16\Omega$, $V_{ol} = \max.$

Motor governor: $I_m = 100mA$














Application Note



Package Dimensions

SSOP24-P-300-1.00

Unit : mm



Weight: 0.32g (typ.)

About solderability, following conditions were confirmed

- Solderability

- (1) Use of Sn-63Pb solder Bath

- solder bath temperature = 230°C
 - dipping time = 5 seconds
 - the number of times = once
 - use of R-type flux

- (2) Use of Sn-3.0Ag-0.5Cu solder Bath

- solder bath temperature = 245°C
 - dipping time = 5 seconds
 - the number of times = once
 - use of R-type flux

RESTRICTIONS ON PRODUCT USE

030619EBA

- The information contained herein is subject to change without notice.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.